



Technical Specifications

Frequency Range	0.3 - 3000 MHz				
Impedance (Nom.)	75 Ohm				
Amp. Rating (measured)	5.0 A @10°C increase				
(calculated)	7.0 A @20°C increase				
Transfer Impedance (CoMeT)	Class A+				
	<0.9 mΩ/m @ 5-30MHz				
	<0.06 mΩ/item @ 5-30MHz				
Screening Attenuation(CoMeT)	Class A++				
	>110 dB @ 30-1000MHz				
	>105 dB @ 1000-2000MHz				
	>100 dB @ 2000-3000MHz				
Return Loss (IEC 61169-1)	Better than	Typical	Insertion Loss Max.	Better than	Typical
0.3 - 500 MHz	-34 dB	-36,6 dB	0.3 - 500 MHz	-0.06 dB	-0.01 dB
500 - 860 MHz	-34 dB	-36.5 dB	500 - 860 MHz	-0.06 dB	-0.01 dB
860 - 1000 MHz	-34 dB	-36.5 dB	860 - 1000 MHz	-0.06 dB	-0.01 dB
1000 - 1750 MHz	-34 dB	-36.4 dB	1000 - 1750 MHz	-0.06 dB	-0.01 dB
1750 - 2150 MHz	-34 dB	-36.4 dB	1750 - 2150 MHz	-0.06 dB	-0.01 dB
2150 - 3000 MHz	-29 dB	-32.1 dB	2150 - 3000 MHz	-0.06 dB	-0.01 dB
Temperature			Intermodulation	IM3	
Installing	-5° to +50° C		3rd Order (@2x+27dBm)	-160 dBc	
Operating	-40° to +70° C				
Storing	-40° to +70° C		Inner Conductor Resistance		
			(@ 1 A DC)	<1.0 mΩ	
Sealing Test			Insulation Resistance		
(IEC IP-code)	IP X8 30 meter / 8 hours		(@ 500 VDC)	>200 GΩ	
			Dielectric Strength		
O-rings	EPDM		DC Test Voltage	>3.0 KV	
Base Material			Max. Tensile Strength		
Body Parts	Brass CuZn39Pb3		Overall	>933 N	
Inner Conductor	Brass CuZn39Pb3			>500 N	
Plating			Torsional Strength		
Body Parts	Nitin-6		(Connector / Cable)	>5.0 Nm	
Inner Conductor	Nitin-6		Test performed by	Søren B. Sørensen	
Insulators	COC (Topas) / PP with Glass		Date of release	December 23, 2013	

Remarks * All tests performed using instruments calibrated in accordance to our ISO 9001 certification. Further technical specifications and installation instructions can be obtained on request.



Connecting with quality!