

### CAT6A UTP KS180W/S

Art.nr. 400-009 / 109



# TOOLLESS CONNECTOR



Art.nr. 400-108

CAT8 STP RJ45 TL-S

#### **Short Description**

With this connector, you can quickly connect a network cable to an RJ45 plug. The connector can be installed without any tools and is easy to open and close with a click. You can also determine the length of the network cable yourself! The connector has a zinc housing, making it strong and durable.

#### **Specifications**

- Color: Silver
- Connector A: RJ45 (8/8) male
- AWG: 22 26
- Speed: up to 40 Gbps
- Bandwidth: 2000 MHz
- Connection type: RJ45
- Operating temperature: -10 to 60 °C
- Version: CAT8.1
- Power over Ethernet: yes

#### **Properties**

- RJ45 connector
- Suitable for Cat8 STP cables
- Cable diameter: 5 to 8.5 millimeters
- Conductor diameter: 1.1 to 1.6 millimeters
- AWG rating for solid core cables: 22 to 26
- AWG rating for stranded core cables: 22 to 26
- Conductor diameter: 1.1 to 1.6 millimeters
- Speeds up to 40 Gigabit
- Zinc housing
- Toolless installation



Connecting with quality!

## **Mounting instructions**

#### Specification notes:

#### **Electrical:**

- 1. RJ45 HousingIPC
- 2. Phosphor Bronze with 50-60 micro-inch Nickel plated.
- 3. Contact areal 50 micro-Inch Gold plated
- 4. IDC Housing PC
- 5. IDC Terminal material & finished:
  - Phosphor Bronze with 50 micro-Inch
  - Tin-Lead plated. Over 50-60 micro-Inch
  - Use for 22-26 AWG stranded and solld wire Nickel plated.
- 6. PCB FR4

#### **Performance**

- a. The IDC color combine two wirings of T568A & T568B.
- b. Retention Strength: 7.7kgs between Jack and Plug
- c. Operation Temperature &°C to 70°C.
- d. Durabilityı
  - Jack 750 cycles Plug-Jack mating and unmating test.
  - IDC Max 200 punching times.









