



Art.nr. 200-122
KOKWI-KOSWI 5-S

KOKWI 5

Art.nr. 200-022



RIGHT-ANGLE IEC FEMALE CONNECTOR

Short Description

Nettrixx IEC and F connectors deliver exceptional shielding performance, exceeding Class A++ standards for optimal 4G (LTE) interference protection. Optimized for ECA jacket triple shielded coax cable.

The innovative compact design fits seamlessly behind ultra-slim smart TVs, making it ideal for modern, spaceconstrained setups. A patented design with built-in strain relief enhances durability and reliability, ensuring long-term performance under everyday use.

With only two parts, the connector is designed for the easiest push-on installation, saving time and effort. The skinfriendly plastic cap adds a touch of ergonomic comfort, ensuring user-friendly handling. Choose these IEC and F connectors for a perfect balance of performance, convenience, and durability.

Properties

- Supports DOCSIS® 4.0 and next-generation broadband
- Quick-twist mounting cap
- Superior A++ screening for effective LTE and wireless ingress protection
- Precision connectors minimize signal loss
- Durable for thousands of installation cycles
- Made with recyclable, eco-friendly materials

Mechanical specifications

- Dimensions (L x W x H): 24 x 8 x 12 mm
- Weight: 0,15 kg

Specifications

- Frequency Range: min 5 - max 1000 MHz
- Impedance: 75 Ohm
- Equipment Approval: CE
- Material: Nickel plated - brass - Tin plated PP
phosphor bronze - HD PE - Nickel plated - brass



Connecting with quality!



Art.nr. 200-122
KOKWI-KOSWI 5-S

KOSWI 5

Art.nr. 200-023



RIGHT-ANGLED IEC MALE CONNECTOR

Short Description

Nettrixx IEC and F connectors deliver exceptional shielding performance, exceeding Class A++ standards for optimal 4G (LTE) interference protection. Optimized for ECA jacket triple shielded coax cable.

The innovative compact design fits seamlessly behind ultra-slim smart TVs, making it ideal for modern, spaceconstrained setups. A patented design with built-in strain relief enhances durability and reliability, ensuring long-term performance under everyday use.

With only two parts, the connector is designed for the easiest push-on installation, saving time and effort. The skinfriendly plastic cap adds a touch of ergonomic comfort, ensuring user-friendly handling. Choose these IEC and F connectors for a perfect balance of performance, convenience, and durability.

Properties

- Supports DOCSIS® 4.0 and next-generation broadband
- Quick-twist mounting cap
- Superior A++ screening for effective LTE and wireless ingress protection
- Precision connectors minimize signal loss
- Durable for thousands of installation cycles
- Made with recyclable, eco-friendly materials

Mechanical specifications

- Dimensions (L x W x H): 24 x 8 x 12 mm
- Weight: 0,15 kg

Specifications

- Frequency Range: min 5 - max 1000 MHz
- Impedance: 75 Ohm
- Equipment Approval: CE
- Material: Nickel plated - brass - Tin plated PP
phosphor bronze - HD PE - Nickel plated - brass



Connecting with quality!